



Important information -
please read carefully!

Securing of loads

2/2

2. Equipment and aids

- Certified friction mats for each row of pallets which are at least 0.8 cm thick
- 15 straps with a blue label, 2,500 daN (old designation: approx. 2,500 kg), for each row of pallets
- 15 long-lever tension ratchets, with a tension force of 500 daN (old designation: approx. 500 kg)
- 30 edge beams (plastic hollow profiles as approved by the BDG [German Gypsum Industry Association] or aluminum edge beams, at least 1 meter in length) to protect the packaging when securely lashed

Please always carry these with you*



Friction mats



Suitable edge
protection



Suitable tension straps (2,500 daN)
with blue label



Suitable tension ratchets
(pre-tension: 500 daN)

3. Procedure

- Secure the load by lashing at the bottom
- Secure the load by lashing across the top



Lashing at
the bottom



Lashing across the top



This Dorfner load is secured correctly

If you have any questions about Dorfner's safety regulations for logistics companies, please contact us:

Michael Bäuerle,
Head of Supply-Chain-Management
Tel: +49 (0) 9622/82-207
Cell: +49 (0) 175/9355025
michael.baeyerle@dorfner.com

Johann Scherer,
Loading Foreman
Tel: +49 (0) 9622/82-161
Cell: +49 (0) 175/9355020
johann.scherer@dorfner.com

* Forgotten anything? You can buy equipment to secure your load at Dorfner.